

Sr.No	Item of work	Qty	Rate	Unit	Amount
	trap/granite/quartzite/gneiss metal for R.C.C.chajja as with C.M. 1:3 of sufficient minimum thickness to give a special finish is to be provided & curing etc. complete.	112.25	5168.14	Cum	580124
14	Providing internal cement plaster 12mm. thick in single coat in cement mortar 1:4 without neeru finish to concrete or brick surfaces, in all positions including scaffolding & curing etc. complete. [Spec.No. :Bd.L.2 Page No. 368]	6500.00	100.00	Sqm	650000
15	Providing sand faced plaster externally in cement mortar using Kharsalia/Kasaba or similar type of sand,in all positions including base coat of 15mm. thick in C.M. 1:4, using waterproofing compound at 1kg.per fourteen days, scaffolding etc.complete.	1400.00	350	Sqm	490000
16	Providing and laying Ceramic Tiles flooring 20 mm to 25 mm thick in plain pattern on a bed of 1:6 cement mortar including cement float,filling joints with neat cement slurry, curing, polishing and cleaning etc.	961.00	1250	Sqm	1201250
17	Providing and fixing white glazed tiles 200mm.x100 mm.in size and about 5 to 6 mm. thick for dado and skirting in required position on plaster of 1:4 cement mortar and neat cement float including filling joints with white cement slurry curing and cleaning etc. complete.	865.00	679.374	Sqm	587659
18	Providing and laying white glazed tiles 200mm.x100 mm.in size and 5 mm.to 6 mm. thick for flooring in required position laid on bed of 1:4 cement mortar including neat cement float,filling joints with white cement slurry curing and cleaning etc. complete. [Spec.No. :Bd.M.12 Page No. 385]	651.00	634.374	Sqm	412977
19	Finishing the terrace slab integrally mixed with white cement & water- proofing compound in C.M.1:3 with 12mm. Thick layer including curing,finishing using waterproof compound at the rate,of 1Kg.per bag of cement etc.complete. [Spec.No. : As directed by Engineer incharge.]	321.00	350.00	Sqm	112350
20	Providing & applying washable oil bound distemper of approved colour & shed to new surfaces in two coats including scaffolding & preparing the surfaces [excluding primer coat] etc. complete.	6500.00	80	Sqm	520000
21	Providing and applying two coats of water proof cement paint of approved manufacture and of approved colour to the plastered surfaces including surface, watering for two days etc. complete.	1400.00	180	Sqm	252000

page 3

Sr.No	Item of work	Qty	Rate	Unit	Amount
22	Providing and fixing in position alluminium louvered windows / ventilators of various sizes with powder coating as per detailed drawing and specifications including alluminium frames 80mm x approved quality etc. complete. [As directed by	176.61	4500	Sqm	794745
23	Providing and Fixing factory made precast door/ window frames of C.C.M-40 grade of section 100 mm.x 60 mm. including reinforcement as per I.S.6523 with polymeric blocks having screw holding capacity of 250 kg / screw fixed in position in R.C.C etc. complete.	325.85	315	Sqm	102643
24	Providing and fixing in position steel reinforcement of various diameters for R.C.C.pile caps, footings, foundations, slabs, beams, columns canopies, staircase, newels, chajjas, lintels, pardis, copings, fins, arches etc. as per detailed designs, drawings and schedules. including cutting, bending, hooking the bars, binding with wires or tack welding and supporting as required etc. complete. [Spec.No. :Bd.F.17 Page No 306.]	44.92	61500.0	M.T.	2762580
25	Providing and casting in situ cement concrete M-20 of trap/ granite/ quartzite/ gneiss metal for R.C.C.waist slab , and steps 'as per detailed drawings for staircases including centering, formwork, compaction, finishing the formed surface with C.M. 1:3 of sufficient minimum thickness to give a smooth and even surface or roughening the surface if special finish is to be provided and curing etc complete. (Excluding reinforcement). [Spec.No. :Bd.F.13 Page No. 305/IS:456(2000)]	62.10	6500.00	Cum	403650
26	Providing 2nd class brick masonry with conventional size bricks (confirming to I.S.12894:1990) in C.M.1:4 in Half brick thick wall including 75 mm thick band in C.C. 1:2:4 after every Eleventh layer with mild steel Longitudinal reinforcement of 2 bars of 6 mm diameter, scaffolding, racking out joints and watering etc. complete. (The C.C.	334.65	550.00	Sqm	184058
27	Providing and fixing solid core flush door commercial in single leaf 35 mm. thick without ventilator commercial type of exterior grade confirming to I.S.2202-1966 (Revised) as per three coats with one coat of primer etc. complete. [Spec.No. : As directed by Engineer in charge.]	225.00	3500	Sqm	787500
			Total Rs.		16500028
	Add for Supervision 3.5 %		Rs.		577501